

1. General Description

This Document contains the log data of a read out logfile. It shows what happened with the specified vbar unit during the latest time

Version of PC Software	5.3.2b 31.12.2012
Date	Mon Nov 07 09:20:15 EET 2016
Serial	1410043376
Prod Date	21.7.2014 10:23
Firmware	5.3
Patchlevel	4

2. Chronological List of Events

▶	0:16	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	0:26	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	0:28	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✔	0:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:11	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	1:13	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✔	1:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:44	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	1:46	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	1:46	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	1:53	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	1:53	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	1:54	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	1:58	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	1:58	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	2:00	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	2:01	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	2:11	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	2:12	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✔	2:22	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:32	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✓	2:42	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:52	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	2:57	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	3:03	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	3:04	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	3:06	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	3:06	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	3:07	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	3:09	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✓	3:19	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	3:23	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	3:29	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✓	3:39	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	3:43	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	3:44	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✓	3:54	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	4:04	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	4:08	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	4:08	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
✓	4:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	4:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	4:30	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✓	4:40	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	4:50	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	5:00	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	5:06	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	5:07	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	5:09	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.

▶	5:10	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	5:15	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✔	5:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:35	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	5:43	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	5:51	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	5:51	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	5:54	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	5:54	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
✔	6:04	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:14	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	6:19	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	6:22	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
✔	6:32	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:42	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	6:45	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
✔	6:55	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	7:02	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	7:05	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	7:07	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
✔	7:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:27	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	7:34	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	7:34	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	7:35	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	7:38	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.

	7:38	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	7:41	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	7:41	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	7:43	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✔	7:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	8:18	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✔	8:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:48	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:58	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	9:08	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	9:18	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	9:28	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	9:38	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	9:39	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	9:41	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	9:41	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	9:42	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
✔	9:52	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	10:02	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	10:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	10:22	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	10:32	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	10:37	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	10:37	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	10:38	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.

✓	10:4 8	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	10:5 8	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	10:5 9	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	11:0 1	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	11:0 1	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
	11:0 3	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
▶	11:0 4	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
▶	11:0 6	Governor Sensor no Signal	The Sensor does not deliver a usable Signal. This happens if the Rotor does not move, or if the Sensor fails during flight.
	11:0 6	Governor Sensor Signal Failure	The Sensor delivers a Signals that has too high frequency. This usually points to a defect of the wire or noise that is coupled into the sensor wire.
✓	11:1 6	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	11:2 3	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
✓	11:3 3	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	11:4 3	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	11:5 3	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	12:0 3	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	12:0 4	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	12:1 2	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
✓	12:2 2	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✓	12:3 2	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	12:3 4	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	12:4 2	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	12:4 9	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	12:5 1	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	12:5 5	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.
▶	12:5 7	Testmode Started	The testmode ist entered intentionally by the user with the command on a Controlpanel or any other control terminal. The Entering command is checksum tested, so it cannot happen accidentally. In Testmode the normal control loop algorithm is not running, so its important to leave the Testmode prior flight. Its only can happen to fly in testmode with bluetooth.

▶	13:07	Testmode Ended	Testmode has been switched off intentionally. Normal control loop is in action now
✔	13:17	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	13:23	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	13:29	Governor ON	Governor switched to mode ON
▶	13:31	Governor ON	Governor switched to mode ON
▶	13:31	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	13:33	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	13:36	Governor ON	Governor switched to mode ON
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
⚠	0:01	Init Failed, retrying...	The Init process of the sensors is very sensitive to movements of the heli or from other external disturbances, i.e. Voltage jumps and glitches. This can lead to a failed initialization. In this Case it is repeated. If this repeats itself all the time, this can point to a defective sensors.
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:23	Governor ON	Governor switched to mode ON
✔	0:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:35	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	0:45	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:55	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:05	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	1:19	Governor ON	Governor switched to mode ON
▶	1:20	Governor ON	Governor switched to mode ON
▶	1:20	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	1:21	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	1:31	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:41	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:51	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✔	2:01	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:05	Governor ON	Governor switched to mode ON
✔	2:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:24	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	2:33	Governor ON	Governor switched to mode ON
▶	2:34	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	2:44	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:54	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:04	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:14	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✔	2:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	2:53	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	3:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✔	5:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	6:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	7:03	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	7:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	7:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:33	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:43	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	8:53	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	9:03	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	9:13	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	9:23	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	9:31	Governor ON	Governor switched to mode ON
⚠	9:37	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.

▶	9:46	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	9:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	10:05	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	10:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	10:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	10:35	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	10:44	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	10:54	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	11:03	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	11:13	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	11:22	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	11:32	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	11:42	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	11:52	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	12:02	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	12:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	12:22	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	12:23	Governor is at Low Throttle Limit	There is a defined low limit, that the Governor will not fall below. If this Limit is reached, this Info Message is issued. The Message is issued once for each touch of the limit. If the limit is touched, it means that your headspeed will be higher than programmed.
⚠	12:30	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✖	12:39	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
▶	12:49	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	12:59	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	13:09	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	13:18	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
✖	13:27	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations

▶	13:3 7	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	13:4 7	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	13:5 6	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	14:0 6	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	14:1 6	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	14:2 6	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	14:3 6	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	14:4 6	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	14:5 6	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	15:0 6	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	15:1 3	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	15:2 3	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	15:3 3	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	15:4 2	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	15:5 2	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
✔	16:0 2	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
⚠	16:1 1	High Vibration Level	The control loop suffers from a high vibration level, that starts to render the sensors blind. Save flying is possible, but the stability will be degraded. Additionally slow drifts that happen may be caused by vibrations.
▶	16:2 1	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
▶	16:3 0	Raised Vibration Level	There was detected a raised level of Vibration. Since the vibration detector has to decide which signal is vibration and this is the intended measurement signal, this can happen sometimes on hard 3d moves. It shall not happen all the time. If this error is reported repeatedly very often, check the heli for vibration sources.
⚠	16:3 1	The Cyclic Ring is active	If the agility of a Heli is set to the possibilities of the mechanic and aerodynamic limits, this did not happen. However in 3D Flying the agility cannot set high enough to fulfill the pilots needs. So this limiter is in action dependant on the flown actions. If it is active very often, there is a potential problem with the mechanics. Using lighter blades will help increasing the natural agility preventing hitting the cyclic ring all the time.
✖	16:3 1	Aileron Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handled on ground, or on very hard landings or very extreme Vibrations.
✖	16:3 1	Elevator Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handled on ground, or on very hard landings or very extreme Vibrations.
✖	16:3 2	Aileron Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handled on ground, or on very hard landings or very extreme Vibrations.
✖	16:3 2	Elevator Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handled on ground, or on very hard landings or very extreme Vibrations.

⚠	16:3 2	Tail Sensor shows no actual Signal	This is an plausibility check. If the Heli starts to vibrate, this shall at least have effect to all sensors. If one of the Sensors do not show the Signal, it may point to a specific problem, not necessary with this sensor, but a general problem.
✖	16:3 3	Aileron Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handleed on ground, or on very hard landings or very extreme Vibrations.
✖	16:3 3	Elevator Sensor Value out of Range	The Sensor delivers Values that are not trustful. Rotational rates, that will create this values are usually not possible in air. The Sensor may be defective. This can happen in certain cases if the heli is handleed on ground, or on very hard landings or very extreme Vibrations.
▶	16:3 3	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✖	16:4 0	Extreme Vibration Level	Vibrations are extreme. That means, that the measurement signal is much lower than the signal level of the vibrations. No usable flying is possible with this level. Everything has to be checked and extended tests are needed to isolate and eliminate the source of vibrations
✔	16:5 0	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	17:0 0	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	17:1 0	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	17:2 0	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor ON	Governor switched to mode ON
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:05	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:35	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:37	Governor ON	Governor switched to mode ON
▶	0:37	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:38	Governor ON	Governor switched to mode ON
▶	0:38	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:39	Governor ON	Governor switched to mode ON
▶	0:39	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:41	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:42	Governor ON	Governor switched to mode ON
▶	0:48	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:50	Governor ON	Governor switched to mode ON
✔	1:00	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:10	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

▶	1:13	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	1:17	Governor ON	Governor switched to mode ON
▶	1:22	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	1:32	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:42	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:52	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:02	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor ON	Governor switched to mode ON
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

✔	1:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:24	Governor ON	Governor switched to mode ON
▶	0:32	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:33	Governor ON	Governor switched to mode ON
▶	0:40	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	0:50	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:00	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:10	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:20	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:30	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:40	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:50	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:00	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:05	Governor ON	Governor switched to mode ON
✔	2:15	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	2:22	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	2:32	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:42	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:52	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds

▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor ON	Governor switched to mode ON
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:26	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:27	Governor ON	Governor switched to mode ON
▶	0:29	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:30	Governor ON	Governor switched to mode ON
✔	0:40	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	0:50	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	1:00	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.
✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:00	Coldstart	A Coldstart is done on the beginning of each switch on time. A Coldstart can happen only, if the VBar Units is disconnected from power for more than 5 Seconds.

✔	0:00	Reset Reason: Power On	This happens if power is applied to the VBar unit. Usually this is ok, but it shall never happen in operational mode. So if a reset happens during flight, this points to a power problem. During flight the power on reset results in a warmstart. If a coldstart happens during flight, the power loss was more than 5 Seconds
▶	0:00	Bank 0 Loaded	Bank 0 was loaded from the non volatile memory. This can be triggered my manual backswitch from the userinterface as well as in flight if bank switch is programmed to the aux channel. On Startup the Bank 0 is loaded by default.
▶	0:00	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	0:06	Calibration Finished	At each Coldstart, the sensor and RC Values are calibrated to the actual seen values. If the calibration is finished, this message confirms the storage of data into the internal non volatile calibration memory
✔	0:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	0:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	1:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:16	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:26	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:36	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:46	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	2:56	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	3:06	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	3:15	Governor ON	Governor switched to mode ON
✔	3:25	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
▶	3:27	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	3:28	Governor ON	Governor switched to mode ON
▶	3:29	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	3:35	Governor ON	Governor switched to mode ON
✔	3:45	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.

▶	3:48	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	3:54	Governor ON	Governor switched to mode ON
▶	3:55	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	3:58	Governor ON	Governor switched to mode ON
▶	3:59	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
▶	4:00	Governor ON	Governor switched to mode ON
▶	4:02	Governor Mode Throttle	Governor off, the servo moves with the throttle input channel
✔	4:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:22	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:32	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:42	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	4:52	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:02	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:12	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.
✔	5:22	Good Health Message (10sec)	This Message describes the good health state. That means, that the VBar unit does not see any error or Info Message in the last 10 Seconds.